



ALR-H450

ANDROID CONNECTED HANDHELD RFID READER

The ALR-H450 is a robust “connected” **Android** handheld reader enabling users to deploy manageable world class GS1 Gen 2 RFID solutions for supply chain, manufacturing, and asset management applications.

FEATURES

- Full QWERTY keyboard allows easy data entry
- ETSI 865.6–867.6 MHz or FCC/IC 902–928 MHz
- ERP 2W/EIRP 3.3W
- 2D imager supporting all major 1D / 2D barcodes
- **Ergonomic** design provides superior user comfort and use
- Supports Wi-Fi, Bluetooth and 3G cellular connectivity
- **Robust** IP64 sealing for dust and water resistance
- **Prolonged usage** enabled by 3,200 mAh main Li-Po main battery pack and 5,200 mAh gun handle batteries
- Android 4.4 (Kit Kat) OS



APPLICATIONS

- Retail
- Warehouse
- Work in Progress
- Transportation
- Missing item location

Benefit	Enabled By:	What does this mean to me?
Ease of Use	<ul style="list-style-type: none"> • Full QWERTY keyboard • Dual high-power lithium-polymer batteries • Open source Android software development 	<ul style="list-style-type: none"> • Simplifies data input • All day usage without recharging • Easy to provide custom apps
High Performance	<ul style="list-style-type: none"> • Unique high-performance, high gain antenna (unusual for a handheld) • Quad-core 1.3GHz CPU's 	<ul style="list-style-type: none"> • Better read range than most handheld RFID solutions • Reads and processes tag data faster • Runs Android apps faster
A fully “connected” handheld	<ul style="list-style-type: none"> • WiFi 802.11 b/g/n • 3G cellular built in • Bluetooth 4.0 	<ul style="list-style-type: none"> • Wireless simplicity • Always connected • Allows connection to corporate networks
Robust Design	<ul style="list-style-type: none"> • Dust and water ingress protection (IP64) • Solid drop tested design (1.0m/3ft) 	<ul style="list-style-type: none"> • Shock-resisant rubber seals used to ensure durability giving full IP64 water/dust proofing and 1.0M/3ft drop qualification



Android Connected Handheld RFID Reader

High Performance, Easy to Use, Easy to Manage, Easy to Deploy

Fully featured and ready to use out of the box, ALR-H450 comes equipped with a 1D / 2D bar code scanner and WiFi connectivity for ease of connection to your corporate network. A microSD memory expansion slot is included for additional local storage.

Features included are:

- 1D and 2D bar code reader
- Bluetooth/WiFi
- GPS (for location aware applications)
- 3G cellular connectivity for use beyond corporate WiFi areas
- 1/2 Watt speaker
- Microphone
- Light sensors, proximity sensors and G-sensors
- Micro-SD expansion slot

All units are offered in regional frequency options including "US," "Europe," "China" and others

Baseline Specification	ALR-H450
RFID Reader	EPC C1 GEN2 / ISO18000-6C
RFID Power	1W (+5dBm to +30dBm)
Antenna	1dBiL / 4 dBic (Circular)
Scanner	2-D bar code (752 x 480 pixels)
WLAN	Wireless WLAN 802.11 b/g/n
WWAN *	WCDMA/HSDPA/HSPA+ (850/1900/2100MHz), GSM/GPRS/EDGE (850/900/1800/1900MHz) 1 PSAM + 1 SIM
WPAN	Bluetooth v2.1+EDR, v3.0+HS and v4.0
Location Services	GPS (embedded A-GPS)
Communications	Micro USB
Operating System	Android 4.4.2 (Kitkat)
Display	4" TFT-LCD touch screen with backlight, 16.7M colors, 480 x 800 (WVGA)
CPU	Cortex-A7 1.3GHz quad-core
Memory	1GB RAM / 4GB Flash
Memory Expansion	MicroSD (32GB Max)
Battery (lithium polymer)	Main 3.7V, 3200 mAh Gun 3.7V, 5200 mAh
Expansion Slot	1 Micro SD slot, 1 SIM slot, 1 PSAM slot

* Due to country specific regulations the cellular modem (WWAN) is not present in units for Singapore or Brazil



Physical Characteristics	
Ingress Protection	IP64
ESD	Contact ± 4KV / ± Air 8KV
Humidity	0-95% at 40°C / 104°F
Operating Temp	-10°C to 50°C / 14°F to 122°F
Storage Temp	-40°C to 70°C / -40°F to 158°F
Weight	371 g / 13.1 oz (no batteries) 448 g / 15.8 oz (with main battery) 623 g / 22.0 oz (with gun handle and all batteries)
Dimensions without gun handle	7.28" (L) x 3.35" (W) x 4.13" (H) 185 mm (L) x 85 mm (W) x 105 mm (H)
Drop	1 meter / 3.28 feet

Model Number	Countries	Frequency	Transmit Channels	Channel Spacing	RF Power	Compliance Certification
ALR-H450	USA, Canada, Colombia, Mexico, Puerto Rico	902 - 928 MHz	50	500 KHz	1 Watt	Emissions: FCC Part 15 Safety: cTUVus tested to: CAN/CSA-C22.2 No.60950-1-03, and UL 60950-1:2007 specifications IEC 60950-1 and EN60950-1, IFETEL
ALR-H450-ARG **	Argentina					
ALR-H450-BRA *	Brazil	902 - 907.5MHz & 915-928 MHz	35	500KHz	1.3 W EIRP	ANATEL Agência Nacional de Telecomunicações
ALR-450-CHN	China	920.5 - 924.5 MHz	16	250 KHz	1 Watt	Agência Nacional
ALR-450-CHN-M *	Singapore	920.5 - 924.5 MHz	16	250 KHz	1 Watt	de Telecomunicações
ALR-H450-EMA	Europe, South Africa, UAE	865.6 - 867.6 MHz	4	600 KHz	1 Watt	Emissions: ETSI EN 302-208-2 (4 channel plan), EN 301-489, ICASA Safety: EN 60950, EN 50360, NRCS
ALR-H450-RSA	South Africa	915.4 - 919 MHz	17	200KHz	4W EIRP	Emissions: ICASA Safety: NRCS
ALR-H450-WR1	Hong Kong	920 - 925 MHz	8	500 KHz	4W EIRP	OFTA

* Due to country specific regulations the cellular modem (WWAN) is not present in units for Singapore (the "-M" signifies no Cellular Modem) and Brazil

** Ships into the country without a power supply (needs to be sourced in country)



Android Connected Handheld RFID Reader

High Performance, Easy to Use, Easy to Manage, Easy to Deploy

The following accessories are included in the ALR-H450 package.

Replacements and additions may be purchased separately using the order numbers indicated below.

Accessories Included	
Ordering Information	Description
ALX-520	ALR-H450 Pistol Grip
ALX-521	ALR-H450 Pistol Grip Battery
ALX-522	ALR-H450 Flat Main Body Battery
ALX-523	ALR-H450 Break-out Connector
ALX-524	ALR-H450 Dock with USB On-The-Go Support (OTG). OTG supports the Plugable USB 2.0 OTG Micro-B to 10/100 Network Adapter (not supplied) http://plugable.com/products/usb2-otge100
ALX-525	ALR-H450 USB Cable
ALX-526-1	ALR-H450 Power Adapter US (In US kit ALR-H450 only)
ALX-526-2	ALR-H450 Power Adapter Europe (In Europe kit ALR-H450-EMA only)
ALX-526-3	ALR-H450 Power Adapter China (In China kit ALR-H450-CHN only)



The ALX-526 does not ship to Argentina and Brazil has a different model number.

May 21, 2018

Copyright © 2018 Alien Technology LLC. All rights reserved.

Alien, Alien Technology, the Alien Technology logo, Spider, Higgs, Dynamic Authentication, QuickWrite, BlockWrite, Squiggle, and the Squiggle logo are trademarks or registered trademarks of Alien Technology Corporation in the U.S. and other countries.

HANDLING PRECAUTIONS Observe standard handling practices to minimize ESD.

DISCLAIMER Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

This product is covered by one or more of the following U.S. patents: 7716208, 7716160, 7688206, 7671720, 7659822, 7619531, 7615479, 7598867, 7580378, 7576656, 7562083, 7561221, 7559486, 7559131, 7554451, 7411503, 7385284, 7377445, 7364084, 7353598, 7342460, 7324061, 7321159, 7301458, 7295114, 7288432, 7265675, 7262686, 7215249, 7214569, 7199527, 7193504, 7173528, 7172910, 7172789, 7141176, 7113250, 7101502, 7080444, 7070851, 7068224, 7046328, 6998644, 6988667, 6985361, 6980184, 6970219, 6952157. Other patents pending.

This product is licensed under patents of Round Rock Research, LLC, for use solely with UHF RFID Readers (such as Alien reader products) that are licensed under an agreement with Round Rock Research, LLC.



Alien Technology
845 Embedded Way.
San Jose, CA 95138
www.alientechnology.com